

Specifications

Model	EK6075 PRO 2WD	EK6075 PRO 4WD	EK6090 PRO 2WD	EK6090 PRO 4WD	EK6090 X-PRO 4WD
Engine					
Model	E4.286TCI	E4.286TCI	E4.368TCI	E4.368TCI	E4.368TCI
Make	Escorts Ltd.	Escorts Ltd.	Escorts Ltd.	Escorts Ltd.	Escorts Ltd.
Number of cylinders	4	4	4	4	4
Engine power @ rated rpm	HP 74.5	74.5	88	88	88
Displacement	cc 2860	2860	3680	3680	3680
Rated RPM	rpm 2200	2200	2200	2200	2200
Fuel tank capacity	ℓ 60	60	75	75	100
Air cleaner	Dry, dual	Dry, dual	Dry, dual	Dry, dual	Dry, dual
Transmission					
Gear			F12 / R12		
Type			Synchro Mesh		
Clutch type			Double		
Brake type			Wet disc (OIB)		
Max. traveling speed					
Forward	km/h 34.2			37.8	
Reverse	km/h 25.6			28.3	
PTO					
Speed	rpm 540 / 1000			540 / 540E	
Output	HP 65			73.5	
Type			Independent & Ground PTO		
3-point hitch			Cat. II		
Hydraulics					
Control system			Draft & position		
Lift capacity (at lower link end)	kg 2500				3000
Lift capacity (at 610mm behind lifting pt.)	kg 1219				1886
Auxiliary valve			2 single & double acting (convertible)		
Steering			Power steering		
Tyre					
Front standard tyre	7.5-16, R1	11.2-24, R1	9.0-16, R1		12.4-24, R1
Rear standard tyre	16.9-30, R1	16.9-30, R1	18.4-30, R1		18.4-30, R1
Dimensions					
Overall length	mm 4190	4165		4190	
Overall width	mm 1940	1830		1940	
Overall height	mm 2550	2455		2550	
Wheel base	mm 2355	2355		2300	
Ground clearance	mm 440	400		405	
Front tread width	mm 1380 - 1620	1525 - 1735		1540 - 1900	
Rear tread width	mm 1500 - 1900			1508 - 1908	
Turning radius w/o brake	m 3.9	4.7	4		4.6
Tractor weight (Unballasted)	kg 2782	2932	3115	3265	3371
(Fully ballasted)	kg 3196	3346	3461	3681	3659

Standard attachment

Model name	EK6075 PRO 2WD	EK6075 PRO 4WD	EK6090 PRO 2WD	EK6090 PRO 4WD	EK6090 X-PRO 4WD
Rear wheel weight		4 pieces (39 kg x 2 + 32 kg x 2)			-
Front weight	5 pieces (40 kg x 1 + 22 kg x 4)			4 pieces (35 kg x 4)	
Front weight bracket	Standard			Standard as battery box	
Rear tow hook	Rotating swivel type			-	
Front work light			Standard		
Rear work light			Standard		
Swinging draw bar			Standard		
ROPS (Certification)			Standard (OECD)		
Canopy			Standard		

Optional attachment

Model name	EK6075 PRO 2WD	EK6075 PRO 4WD	EK6090 PRO 2WD	EK6090 PRO 4WD	EK6090 X-PRO 4WD
Rear wheel weight		Max. 2 pieces (32 kg x 2)			Max. 2 pieces (39 kg x 2)
Front weight		-		Max. 2 pieces (35 kg x 2)	

* ESCORTS LIMITED reserves the right to change the stated specifications without notice.

Manufactured by:

ESCORTS LIMITED

Marketed by:

KUBOTA Corporation



KUBOTA

EK

EK60 PRO SERIES TRACTOR
EK6075 PRO 2WD / 4WD
EK6090 PRO 2WD / 4WD
EK6090 X-PRO 4WD

BASIC · RELIABLE · POWERFUL



EK6090 X-PRO model shown

BASIC • RELIABLE • POWERFUL

EK6075 PRO / EK6090 PRO / EK6090 X-PRO

EK60

PRO SERIES TRACTORS



ENGINE

4 Cylinder, turbo charged, intercooler, direct injection engine

- Ease of all applications without engine RPM drop.
- More output & more saving with better fuel economy.

COMFORT

Power steering

The power steering reduces operator fatigue even during long working hours.

Side shift gear levers

Ergonomically placed gear levers for better comfort and easy operation.

Full flat platform

The wider leg room offers an operator greater comfortability.

3-point hitch external adjustment lever

(only available for EK6090 X-PRO model)
This feature allows you to adjust the rear 3-point hitch from rear side of the tractor. So attaching and detaching implements is quick, easy and precise.

		EK6075 PRO		EK6090 PRO		EK6090 X-PRO
		2WD	4WD	2WD	4WD	4WD
Engine power @ rated rpm	HP	74.5				88
PTO speed	rpm	540/1000				540/540E
Max. traveling speed	km/h	34.2				37.8
Tilt steering		-		-		Standard
3-point hitch external adjustment lever		-		-		Standard
Smart lift		-		-		Standard
Front fenders		-		-		Standard
Fuel tank capacity	ℓ	60		75		100
Tractor weight (Unballasted)	kg	2782	2932	3115	3265	3371



EK6090 PRO model shown



A new brand established by Kubota and Escorts Ltd., E-KUBOTA adds a line of affordable tractors to Kubota's product range. These E-KUBOTA tractors were developed and manufactured by Escorts Ltd. and sold through Kubota's sales network, providing customers with a wide range of reliable tractor models and Kubota's trusted after sales support.

*The optional rear wheels weight are equipped in the picture.

FUNCTIONALITY

Transmission

Synchro Mesh Transmission with 12 Forward + 12 Reverse with Synchro Shuttle.

Hydraulic System

2 single & double acting convertible auxiliary valve.

Multi disc oil immersed brakes (OIB)

Efficient brakes on roads with heavy loads. Enhanced life with low maintenance cost.

Front & rear work lights

Bright Front & rear work lights provide plenty of illumination for night-time tasks.

Smart lift (only available for EK6090 X-PRO model)

Smart lift features for quick lifting and lowering with same working depth of implements during headland turn.

Double clutch for independent PTO

Easy cut-off PTO power while on turns during PTO operation. Gives comfort to operator and enhances clutch life.

3-point hitch

The category II 3-point hitch provides fast and simple attachment of rear-mounted implements.

Lift capacity

2500 kg Lifting capacity at lower link end. (3000kg Lifting capacity for X-PRO model)

