





AUTOMATIC SWING ARM

The PERFECT RF swing arm mower is a great machine to easily mow in the tree line. Its asymetric layout and large offset enable to also work in orchards with larger tree canopies.

When the rubber swing arm protection touches the tree trunk, the disk rotates and deflects the mowing disk gently around the trunk. As soon as the springloaded swinging arm has passed the tree it automatically returns to its original position.





Robust design for professional fruit growers, excellent capacity and easy-to-use. A must have for organic growers.



RF SERIES In-row orchard mower



The heavy v-belt transmission with autometic tensioning ensures an excellent capacity, also in tall grass.

For young trees or when operating on inclines >5% the RF mower can be provided with a hydraulic feeler bar.



Because of its large offset in combination with the swing arm, the RF mower is very well equipped to mow the grass between and underneath solar panels and to cut grass under board fences, along wire or rock fences and around fence posts.



OPTIONS

- Hydraulic offset
- Mechanic-hydraulic feeler system
- Raiseable swing arn
- Rubber wheels

TECHNICAL SPECIFICATIONS	RF-220	RF-340
Cutting width (cm/inch)	220 / 7'3"*	340 / 11'2"*
Min. power required at 540 rpm of pto (kW/HP)	19 / 25	33 / 45
Number of blades	2 + 1	4 + 1
Diameter blade of swing arm (cm/inch)	60 / 23 ^{1/2}	60 / 23 ^{1/2}
Cutting height (cm/inch)	4-14 / 1½-5½	4-14 / 1½-5½
Length of rear roller (cm/inch)	53 / 1'9"	95 / 3'1"
Max. offset from centre of tractor (cm)	215*	297*
Weight (kg/lbs)	495 / 1089	715 / 1573

As our policy is one of continuous improvement, we reserve the right to change the specification or to modify the desing without prior notice



Van Wamel B.V.

Van Wamel B.V.
Energieweg 1, 6658 AE
Beneden Leeuwen
The Netherlands

+31 (0) 487 59 29 44
+31 (0) 487 59 29 44
www.vanwamel.nl
perfect@vanwamel.nl



♥ +27 (0) 11 284 2000 @ www.kubota.co.za

mail@smithpower.co.za